

MATERIAL SAFETY DATA SHEET

WFI-3
Date 07/95
Emergency Telephone # (800) 424-9300 (Chemtrec)



BUILDING PRODUCTS GROUP
ONE SOUTH WACKER DRIVE
CHICAGO IL 60606
PHONE 312 750 0900
FAX 312 263 5808

SECTION 1. MATERIAL IDENTIFICATION

Product Name:

DURON®, DUREX™, DUROSTORE®, STRUCTOBOARD® and DURA-THRIPT® Hardboard, Regular, Shop Grade, Tempered, and/or fill coated, and/or painted, and/or primed, and/or water resistant.

SECTION 2. INGREDIENTS AND HAZARDS % EXPOSURE LIMITS

	%	OSHA	ACGIH
Wood Fiber (use of these products may create wood dust)	less than 98	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TLV-TWA: 5 mg/m ³ (softwoods) STEL: 10 mg/m ³ (softwoods) TLV-TWA: 1 mg/m ³ (hardwoods)
Paraffin Wax (CAS 8002-74-2)	Trade Secret	TWA 2 mg/m ³ (fumes)	
Clay (CAS 1332-58-7)	Trade Secret	TLV 10mg/m ³	
Titanium Dioxide (CAS 13463-67-7)	Trade Secret	TLV 10mg/m ³ PEL 10mg/m ³ - Total 5mg/m ³ - Respirable	
Calcium Carbonate (CAS 00471-34-1)	Trade Secret	TLV 10mg/m ³ PEL 15mg/m ³ - Total 5mg/m ³ - Respirable	
Talc - Non Fibrous (CAS# 14807-96-6)	0 - 3	PEL 20mg/m ³ TLV 2mg/m ³ - Respirable	
Vegetable Oil	1 - 3	PEL 15mg/m ³ - Total 5mg/m ³ - Respirable TLV 10mg/m ³	

SECTION 3. PHYSICAL DATA

SOLUBILITY IN WATER: Nil

SPECIFIC GRAVITY (H₂O = 1): 0.8 - 1.2



an INTERNATIONAL PAPER company