

SECTION 3. PHYSICAL DATA (cont'd)

APPEARANCE AND ODOR: Light brown to brown to gray colored board, low odor.

SECTION 4. FIRE AND EXPLOSION DATA

Flash Point and Method	Autoignition Temperature	Flammability Limits In Air
None	Variable 390° - 500° F	Variable

EXTINGUISHING MEDIA: Water, Foam.

UNUSUAL FIRE/EXPLOSION HAZARDS: Wood Dust requires 0.040 Joules/minutes of energy for ignition and can produce an explosion pressure of 113 psig max.

SPECIAL FIRE FIGHTING PROCEDURES: When exposed to fumes, wear a Self-Contained Breathing Apparatus (SCBA) with full face piece operated in the pressure-demand or positive pressure mode.

COMMENTS: If wood dust is being produced from this product, it should be kept in a cool, dry place away from ignition sources. Hot, humid storage can result in spontaneous combustion.

SECTION 5. REACTIVITY DATA

Avoid contact with oxidizing agents and with drying oils.

SECTION 6. HEALTH HAZARD INFORMATION

STABILITY: Stable.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, Carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

EFFECTS OF OVEREXPOSURE: Avoid prolonged repeated breathing of wood dust in air. Repeated exposures to certain wood dusts can produce such allergenic responses as dermatitis, asthma and bronchitis.