



C O R P O R A T I O N

P.O. Box 4040 Medford Oregon 97501
Telephone (541) 753-7373 Fax (541) 753-4914

=====

SECTION I - IDENTIFICATION

PRODUCT: Exterior medium density fiberboard, wood-based panel product, formaldehyde free

TRADE NAME: Medex

DATE PREPARED: 7/28/95 rev.

=====

SECTION II - HAZARDOUS INGREDIENTS

<u>Ingredient</u>	<u>CAS No.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Mixed Softwood	N/A	TWA-15 mg/m ³ (total) 5 mg/m ³ (respirable)	TWA-5 mg/m ³ STEL-10 mg/m ³ (15 min.)
Methylenebis (Phenylisocyanate)	101-68-8	.02 ppmC	.005 ppm
Paraffinic Wax	8002-74-2	2 mg/m ³	2 mg/m ³
Mineral Wax	N/A	N/A	N/A
Red Dye	N/A	N/A	N/A

=====

SECTION III - PHYSICAL & CHEMICAL CHARACTERISTICS

<u>BOILING POINT:</u> N/A	<u>SPECIFIC GRAVITY:</u> 0.6 - 0.99
<u>VAPOR PRESSURE:</u> N/A	<u>VAPOR DENSITY:</u> N/A
<u>% VOLATILE BY VOLUME:</u> N/A	<u>EVAPORATION RATE:</u> N/A
<u>SOLUBILITY IN WATER:</u> <0.1%	<u>pH (PRODUCT):</u> N/A

APPEARANCE & ODOR: Cherry-blond solid panel; woody odor.

=====

SECTION IV - FIRE & EXPLOSION HAZARDS

<u>FLASH POINT:</u> N/A	<u>AUTO-IGNITION TEMP:</u> Varies (400 - 500 degrees F)
-------------------------	---------------------------------------------------------

FLAMMABLE LIMITS: LEL (wood dust) 40 g/m³

EXTINGUISHER MEDIA: Class A

SPECIAL FIRE FIGHTING PROCEDURES: Use water to wet down wood dust to reduce the likelihood of ignition or dispersion of dust into the air. Remove burned or wet dust to open area after fire is extinguished.